

REMS 4" automatic die head

for pipe threads 2 1/2–4" (page 39).

Nipple-threading

Efficient with the automatic internal clamping REMS Nippelfix 1/2–2" (4") or with the manual internal clamping REMS Nippelspanner 3/8–2" (page 46).

Material supports

Vertically adjustable material supports REMS Herkules and REMS Herkules Y (page 80).

REMS roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25-200 (300), 1–8" (12") (page 50).



Wheel stand (Accessory)

Supply format

REMS Tornado. Threading machine for pipe threads 1/16–2", 16–63 mm, bolt threads 6–60 mm, 1/4–2". With maintenance-free gear, safety foot switch with emergency-stop, 2 automatic chucks, automatic lubrication and cooling. With tool set consisting of one universal automatic die head for all threads, also long threads, automatic opening, with automatic thread-length-stop for tapered threads. Dies for pipe threads, tapered, ISO 7-1, DIN EN 10226 (DIN 2999, BSPT) R 1/2–3/4" and R 1–2" right-hand, pipe cutter, inner pipe deburrer, pressing lever, adjustable height material support. Choice of 3 motors. Portable version with 3 tubular legs, with removable, large oil and chip tray. Version T with integrated, even larger oil basin and chip tray, for work bench, stand or wheel stand with material support.

Description	Version	Art.-No.	€ excl. VAT
2000	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 53 rpm. Portable, 3 legs.	340200	2,850.00
2010	Pole-reversible capacitor, motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running. Portable, 3 legs.	340201	3,060.00
2020	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running. Portable, 3 legs.	340202	3,180.00
2000 T	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 53 rpm. For work bench, stand or wheel stand.	340206	3,360.00
2010 T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running. For work bench, stand or wheel stand.	340207	3,560.00
2020 T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running. For work bench, stand or wheel stand.	340208	3,680.00

Other voltages and NPT versions on request.

Accessories

Description	Art.-No.	€ excl. VAT
Stand (picture see page 35)	344105	202.00
Wheel stand with material support	344100	320.00
Dies see page 38.		
Universal automatic die head quick-change die head instead of changing the dies	341000	488.00
REMS 4" automatic die head for pipe threads 2 1/2–4", see page 39.		
REMS cutter wheel St 1/8–4", s 8	341614	7.80
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports , see page 80.		
REMS roll grooving attachment for pipe grooving, see page 50.	347000	2,120.00

