

Productname :	BRIGHT, COLD GALVANISE	Creationdate :	21.04.08
Ref.Nr.:	UK10108-3-210408	Replaces:	10.03.08

1. IDENTIFICATION OF PRODUCT AND COMPANY

Productname : BRIGHT, COLD GALVANISE
Aerosol

Application : Anti Corrosion Products

Company : CRC Industries UK Ltd.
Castlefield Industrial Estate, Wylds Rd, Bridgwater,
Somerset,
UK, TA64DD
Tel.: (+44)(0)1278 727200
Fax: (+44)(0)1278 425644
E-mail : hse.uk@crcind.com

In case of emergency : (+44)(0)1278 727200

Subsidiaries		Tel	Fax
CRC Industries Europe	Touwslagerstraat 1 9240 Zele Belgium	(+32) (0) 52 / 45 60 11	(+32) (0) 52 / 45 00 34
CRC Industries Finland	Asemanrinne 13, 08500 Lohja AS	(+358)(0)19/32921	(+358)(0)19/383676
CRC Industries France	12, Bld des Martyrs de Chateaubriant F-95102 Argenteuil Cédex	(+33)(0)1/34112000	(+33)(0)1/34110996
CRC Industries Deutschland	Südring 9, 76473 Iffezheim	(+49)(0)7229/3030	(+49)(0)7229/303266
CRC Industries Iberia	Gremio del cuero S/N, 40195 Segovia	(+34)921/427546	(+34)921/436270
CRC Industries Sweden	Kryptongatan 14, 43153 Mölndal	(+46)(0)31/7068480	(+46)(0)31/273991

2. HAZARD IDENTIFICATION

Health and Safety : R12: Extremely flammable.
(DME propellant)
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Environment : R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other hazards : Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.

Remark: The classification for aspiration hazards (R65), does not apply for products placed on the market in aerosol containers. (EU-Directive 67/548 Annex VI 9.4)



Productname : BRIGHT, COLD
GALVANISE
Ref.Nr.: UK10108-3-210408

Creationdate : 21.04.08
Replaces: 10.03.08

3. COMPOSITION AND INFORMATION ON COMPONENTS

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
dimethyl ether	115-10-6	204-065-8	30-60	F+	12	A
n-butyl acetate	123-86-4	204-658-1	1-5		10-66-67	
zinc oxide	1314-13-2	215-222-5	0.25-2.5	N	50/53	
ethyl acetate	141-78-6	205-500-4	5-10	F,Xi	11-36-66-67	
Naphtha (petroleum), hydrotreated light (benzene<0.1%)	64742-49-0	265-151-9	5-10	Xn	10-65-66-67	B,P
Naphtha (petroleum), hydrodesulfurized heavy (benzene<0.1%)	64742-82-1	265-185-4	5-10	Xn,N	51/53-65-66-67	B,P
aluminium powder (pyrophoric)	7429-90-5	231-072-3	1-5	F	15-17	A
Explanation notes						
A : substance with Community workplace exposure limit						
B : substance with national established workplace exposure limit						
P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)						

4. FIRST AID MEASURES

General Advice : If symptoms persist always call a doctor

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water for several minutes
Seek medical advice

Contact with skin : Wash with water and soap.

Inhalation : Fresh air, keep warm and at rest.
Seek medical attention if ill effects occur

Ingestion : Ingestion is unlikely to occur
If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

5. FIRE-FIGHTING MEASURES

Flash point (without propellant): < 0 °C

Explosion limits : upper limit : not available

lower limit : not available

Extinguishing media : foam, carbon dioxide or dry agent

Fire-fighting procedures : Keep container(s) exposed to fire cool, by spraying with water

Unusual exposure hazard : Aerosols may explode if heated above 50°C
In case of fire, do not breathe fumes



Productname :	BRIGHT, COLD GALVANISE	Creationdate :	21.04.08
Ref.Nr.:	UK10108-3-210408	Replaces:	10.03.08

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Shut off all ignition sources
Ensure adequate ventilation

Environmental precautions : Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

Cleaning methods : Absorb spillage in suitable inert material

7. HANDLING AND STORAGE

Handling procedures : Use only in well ventilated areas
Keep away from heat and sources of ignition
Do not spray on a naked flame or incandescent material.
Do not pierce or burn aerosols, even after use.
Do not breathe aerosols or vapours.
Avoid contact with skin and eyes.

Storage procedures : Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Keep in a cool, dry, well ventilated place
Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Control procedures : Ensure adequate ventilation
Keep away from heat and sources of ignition
Take precautionary measures against static discharges

Personal protection : It is advisable to take precautions to avoid contact with skin and eyes when handling the product.
Use only in well ventilated areas

inhalation : In case of insufficient ventilation, wear suitable respiratory equipment.
(Filter type AX)

hands and skin : Wear suitable protective gloves
(butylrubber)

eyes : Wear safety goggles.

Exposure limits :

Hazardous ingredient	CAS-nr	method	
EU established exposure limits:			
dimethyl ether	115-10-6	TWA	1000 ppm

9. PHYSICAL AND CHEMICAL PROPERTIES (for aerosols without propellant)

Apperance : physical state : DME propelled liquid

colour : grey



Productname :	BRIGHT, COLD GALVANISE	Creationdate :	21.04.08
Ref.Nr.:	UK10108-3-210408	Replaces:	10.03.08

odour :	solvent
Melting point/range :	<-20 °C
Boiling point/range :	not available
Relative density :	0.969 g/cm ³ (@ 20°C)
pH :	not applicable
Vapour pressure :	not available
Relative vapour density :	not available
Solubility in water :	Insoluble in water
Partition coefficient n-octanol/water:	not available
Flash point :	< 0 °C
Auto-ignition :	> 200 °C
Viscosity :	not applicable
Evaporation rate :	not available

10. STABILITY AND REACTIVITY

Conditions to be avoided :	Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition
Materials to be avoided :	Strong oxidising agent
Hazardous decomposition compounds :	CO,CO ₂

11. TOXICOLOGICAL INFORMATION

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Skin contact :	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
Eye contact :	May cause irritation.

12. ECOLOGICAL INFORMATION

Other adverse effects :	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not allow to enter public sewers and watercourses
--------------------------------	---

13. WASTE DISPOSAL

Product :	Do not empty into drains. This material and its container must be disposed of in a safe way. Disposal should be in accordance with local, state or national legislation
------------------	---



Productname :	BRIGHT, COLD GALVANISE	Creationdate :	21.04.08
Ref.Nr.:	UK10108-3-210408	Replaces:	10.03.08

14. TRANSPORT

UN-number :	1950
Road/Rail - ADR/RID :	UN1950 Aerosols Class : 2, PG : NA, Class code : 5F, Label : 2.1
Sea - IMDG :	UN1950 Aerosols Ltd Qty Class : 2.1, PG : NA, Label : 2.1
EmS	F-D,S-U
Air - IATA/ICAO :	UN1950 Aerosols, flammable Class : 2.1, PG : NA, Label : RFG
Packing instr. LQ	Y203
PAX	203
CAO	203

15. REGULATORY INFORMATION

Warning symbol(s) :	F+
Risk-phrase(s) :	R12: Extremely flammable. R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.
Safety-phrase(s) :	S2: Keep out of the reach of children. S16: Keep away from sources of ignition - No smoking. S23: Do not breathe spray. S35: This material and its container must be disposed of in a safe way. S51: Use only in well-ventilated areas.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Without adequate ventilation formation of explosive mixtures may be possible.

16. OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.



Productname :	BRIGHT, COLD GALVANISE	Creationdate :	21.04.08
Ref.Nr.:	UK10108-3-210408	Replaces:	10.03.08

***Explanation risk-phrases:**

R10: Flammable.
R11: Highly flammable.
R12: Extremely flammable.
R36: Irritating to eyes.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

This Material Safety Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Material Safety Data Sheet will be sent to you upon simple request or can be found on our website : www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

