



SOCIETÀ ITALIANA TECNOSPAZZOLE

THE PROFESSIONAL CHOICE



Date: 07/10/2008 Customer: WALSH ENGINEERING SUPPLIES LTD Customer's code: 974400	TECHINICAL PRODUCT DATA SHEET
--	--------------------------------------

SIT Code	Item description	Brush Picture
G034511f6001	973 REF GG73 G6x25 IN030 PZ.24 Shaft mounted wheel brush for industrial use, 3 rows with crimped high resistant stainless steel wire Ø0.30 mm; very high wire density, long lasting and very effective in various industrial applications.	
	D = 70 mm S = 20 mm E = 12 mm SHAFT = 6x25 mm MAXIMUM ROTATING SPEED : 15000 RPM	

APPLICATIONS :

- Ideal for work in places with difficult access, interior and hollow surfaces. Used on air or power tools, they are suitable for works at very high speeds.

SAFETY INSTRUCTIONS:

All the instructions enclosed to the brush box shall be strictly observed; in particular, but not only: never exceed MAX-RPM value; individual protective equipment must be worn such as goggles, gloves, face guard and shield, against particles ejection and e dangerous temperature onset; staff members without protections shall not allowed to stay around the worker, check brush locking on the electric tool and its maintenance onto the shaft; filaments should always work by tip, don't exceed with pressure, to be reduced at minimum when brushing sharp edges.



ASSOSPAZZOLE

SPAZZOLE TECNICHE PER L'INDUSTRIA
 SPAZZOLE PER FERRAMENTA E UTENSILERIA
 SPAZZOLE PER AUTOSPAZZATRICI STRADALI E AEROPORTUALI
 PISTE IN PLASTICA PER SCI DI DISCESA, FONDO E SALTO