

	<b>technical data sheet</b>
 	Premiumflex A24P BF INOX

application	grinding wheel for free hand grinding mounted on angle grinders
materials	Stainless steel, construction steel, weldings
technical characteristics	coarse grit structure, good stock removal, good life, free of Fe-, S- and Cl- compounds
working speed	80 m/s
application requirements according to EN 12413 and BGV D12	use of safety guards mandatory, user has to observe the safety instructions
All cutting and grinding wheels are tested to the requirements of EN 12413	

ingredients	special corundum with 98% Alumina, 3% Titanoxid, phenolic resin bonded system with fillers, Reinforcement by fibre glas
-------------	---

available sizes[mm]	type	Max. RPM [1/min]
115 x 6 x 22,23	27	13.290
125 x 6 x 22,23	27	12.220
150 x 6 x 22,23	27	10.190
180 x 6,8 x 22,23	27	8.600
230 x 6,8 x 22,23	27	6.640

Confirmation:



Fritzlar  
technology

**Schleifscheibenfabrik  
Rottluff GmbH**  
Weideweg 17  
D-09116 Chemnitz  
Telefon: 0371 / 36 99 50  
Fax: 0371 / 3 69 95 30 / 30 43 40

The company Schleifscheibenfabrik Rottluff GmbH is certified according to the DIN EN ISO 9001.