

	technical data sheet
 	PromaxCC A30U BF INOX

application	cutting wheel for free hand cutting mounted on angle grinders
material	Steel sheet, thin profiles, stainless steel, non ferrous metals, Aluminum alloys, Titanium, composite materials
technical characteristics	coarse grit structure, best life, free cutting, free of Fe-, S- and Cl- compounds, cool cut and burr free
working speed	80 m/s
application requirements according to EN 12413 and BGV D12	for cutting only, use of safety guards mandatory, user has to observe the safety instructions
All cutting and grinding wheels are tested to the requirements of EN 12413	

ingredients	special corundum with 98% Alumina, 3% Titanoxid, phenolic resin bonded system with fillers, Reinforcement by fibre glas
-------------	---

available sizes[mm]	type	Max. RPM [1/min]
100 x 2,5 x 16	41 / 42	15.280
115 x 2,5 x 22,23	41 / 42	13.290
125 x 2,5 x 22,23	41 / 42	12.220
150 x 2,5 x 22,23	41 / 42	10.200
180 x 2,5 x 22,23	41 / 42	8.600
180 x 3,2 x 22,23	41 / 42	8.600
230 x 2,5 x 22,23	41 / 42	6.600
230 x 3,2 x 22,23	41 / 42	6.600

Confirmed by:



Schleifscheibenfabrik
Rottluff GmbH
Weideweg 17
D-09116 Chemnitz
Telefon: 0371 / 36 99 50
Fax: 0371 / 3 69 95 30 / 30 43 40

The company Schleifscheibenfabrik Rottluff GmbH is certified according to the DIN EN ISO 9001.