

	technical data sheet
 	PromaxCC ZA30Q BF

application	cutting wheel for free hand cutting mounted on hand held cutting off machines
materials	Rail material UIC 60, UIC 100, S33, S49...
technical characteristics	coarse grit structure, good stock removal, in combination with strong machines the best life
working speed	100 m/s
application requirements according to EN 12413 and BGV D12	for cutting only, use of safety guards mandatory, user has to observe the safety instructions
All cutting and grinding wheels are tested to the requirements of EN 12413	

ingredients	special corundum with 96% Alumina and Zirconia, 3% Titanoxid, phenolic resin bonded system with fillers, Reinforcement by fibre glas
-------------	--

available sizes[mm]	type	Max. RPM [1/min]
300 x 3,5 x 20	41	6.400
300 x 3,5 x 22,23	41	6.400
300 x 3,5 x 25,4	41	6.400
350 x 4 x 20	41	5.400
350 x 4 x 22,23	41	5.400
350 x 4 x 25,4	41	5.400

Confirmation:



Fritzlar
technology

**Schleifscheibenfabrik
Rottluff GmbH**
Weideweg 17
D-09116 Chemnitz
Telefon: 0371 / 36 99 50
Fax: 0371 / 3 69 95 30 / 30 43 40

The company Schleifscheibenfabrik Rottluff GmbH is certified according to the DIN EN ISO 9001.