



TECHNICAL DATA

RTD Spray

Metal Cutting Lubricant Spray

TECHNICAL DATA

Description

ROCOL RTD Spray is an aerosol applied metal cutting lubricant consisting of a concentrate of extreme pressure additives. ROCOL RTD Spray applies an economical film metal cutting fluid directly to the cutting zone, particularly in areas where access is difficult.

Outstanding Features

- **Superb cutting performance**
- **Suitable for all ferrous metals**
- **Ideal for reaming, tapping, drilling and general workshop operations**
- **Fast and convenient application**

Directions for use

Shake well before use and spray directly onto workpiece or tool from a distance of 15 - 30 cm. Test compatibility with painted or coated surfaces, plastics and rubbers prior to application. Ensure adequate ventilation.

Technical Data (typical values)

<i>Appearance:</i>	<i>Brown liquid</i>
<i>Solvent:</i>	<i>Pentane</i>
<i>Propellant:</i>	<i>Propane/Butane</i>
<i>Shell 4 Ball</i>	
<i>Weld Load:</i>	<i>>800kg</i>
<i>Load-Wear Index):</i>	<i>179kg</i>
<i>Tapping Torque (316 Stainless Steel):</i>	<i>11.2NM</i>
<i>Silicones:</i>	<i>None</i>
<i>Storage:</i>	<i>Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.</i>

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

RTD SPRAY

Pack sizes and part codes

400ml 53011

Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants, ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700);

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: RTD Spray TDS 5301

Date: Sep-04

TECHNICAL DATA

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.

There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility