

	technical data sheet
 	Premiumflex A30S BF

application	cutting wheel for free hand cutting mounted on angle grinders
materials	Iron metals, construction steel general purpose
technical characteristics	coarse grit structure, high stock removal, good life
working speed	80 m/s
application requirements according to EN 12413	for cutting only, use of safety guards mandatory, user has to observe the safety instructions

ingredients	corundum with 96% Alumina, 3% Titanoxid, phenolic resin bonded system with fillers, Reinforcement by fibre glas
-------------	-----------------------------------------------------------------------------------------------------------------

available sizes [mm]	type	Max. RPM [1/min]
100 x 3 x 16	41 / 42	15.280
115 x 3 x 22,23	41 / 42	13.290
125 x 3 x 22,23	41 / 42	12.220
150 x 3 x 22,23	41 / 42	10.190
180 x 3 x 22,23	41 / 42	8.600
230 x 3 x 22,23	41 / 42	6.640
300 x 4 x 22,23	41	6.400
300 x 4 x 25,4	41	6.400
350 x 4 x 22,23	41	5.400
350 x 4 x 25,4	41	5.400




Confirmation:



Fritzlar

Schleifscheibenfabrik
Rottluff GmbH
 Weideweg 17
 D-09116 Chemnitz
 Telefon: 0371 / 36 99 50
 Fax: 0371 / 3 69 95 30 / 30 43 40

The company Schleifscheibenfabrik Rottluff GmbH is certified according to the DIN EN ISO 9001.

	technical data sheet
 	Premiumflex A30S BF

technology