

	technical data sheet
 	Premiumflex A24/30S BF

application	grinding wheel for free hand grinding mounted on angle grinders
materials	Metal, construction steel, weldings
technical characteristics	coarse grit structure, good stock removal, good life
working speed	80 m/s
application requirements according to EN 12413 and BGV D12	use of safety guards mandatory, user has to observe the safety instructions
All cutting and grinding wheels are tested to the requirements of EN 12413	

ingredients	special corundum with 96% Alumina, 3% Titanoxid, phenolic resin bonded system with fillers, Reinforcement by fibre glas
-------------	---

available sizes[mm]	type	Max. RPM [1/min]
100 x 6 x 16	27	15.280
115 x 6 x 22,23	27	13.290
125 x 6 x 22,23	27	12.220
150 x 6 x 22,23	27	10.190
180 x 6,5 x 22,23	27	8.600
180 x 8 x 22,23	27	8.600
230 x 6,5 x 22,23	27	6.640
230 x 8 x 22,23	27	6.640

Confirmation:

Fritzlar
technology



Schleifscheibenfabrik
Rottluff GmbH
 Weideweg 17
 D-09116 Chemnitz
 Telefon: 0371 / 36 99 50
 Fax: 0371 / 3 69 95 30 / 30 43 40

The company Schleifscheibenfabrik Rottluff GmbH is certified according to the DIN EN ISO 9001.