



Date: 07/10/2008 Customer: WALSH ENGINEERING SUPPLIES LTD

Customer's code: 974400

## **TECHINCAL PRODUCT DATA SHEET**

SIT Code	Description	Brush Picture	
U2108201H000	500 REF U115 M14 ATL05 1/12*  Twisted knots wheel brush Smooth bright steel wire Ø 0.50		
<ul> <li>aggressive brushes, suitable for heavy duty applications at high rotating speed, such as preparation and finishing of seam weldings, deburring and mechanical pickling.</li> <li>removal of slags collected inside narrow slots of any dimension.</li> <li>burrs removal.</li> </ul> MAXIMUM ROTATING SPEED: 15000 RPM		S D	D = 115  mm $S = 25  mm$ $F = M14$ $E = 12  mm$ $Z = 20  Knots$

## **SAFETY INSTRUCTIONS:**

All the instructions enclosed to the brush box shall be strictly observed; in particular, but not only: never exceed MAX-RPM value; individual protective equipment must be worn such as goggles, gloves, face guard and shield, against particles ejection and e dangerous temperature onset; staff members without protections shall not allowed to stay around the worker, check brush locking on the electric tool and its maintenance onto the shaft; filaments should always work by tip, don't exceed with pressure, to be reduced at minimum when brushing sharp edges.



SPAZZOLE TECNICHE PER L'INDUSTRIA
SPAZZOLE PER FERRAMENTA E UTENSILERIA
SPAZZOLE PER AUTOSPAZZATRICI STRADALI E AEROPORTUALI
PISTE IN PLASTICA PER SCI DI DISCESA, FONDO E SALTO